

W R T - 1 0 0

W R T - 1 2 5

W R T - 1 5 0

W R T - 2 0 0

A focus on productivity & profitability

Semi-Automatic Stretchwrap Machines: The Rotary Arm Series

WULFTECTM
INTERNATIONAL

The Wulftec Advantage

Only Wulftec offers all the following features, giving end-users a distinct advantage:

Legendary heavy-duty steel structures on all machines.

- Built strong to last forever
- More stable and secure than plastic
- Minimal risk of damage, even in the harshest environments
- Rock solid performance through high impact loading

NO-THREAD™ powered pre-stretch carriage on all models.

- Fast, safe and easy film loading with no threading required
- 50%-300% pre-stretch ensures increased holding power, optimal film performance and savings as well as a rapid return on investment
- Flexible wrapping patterns, speeds and product sizes
- Even and constant film force applied to the load, including irregular shapes



State-of-the-art AC variable frequency drives on all machines.

- Safe and reliable consistent performance
- Easy monitoring and adjusting
- Completely enclosed circuit with built-in alarm diagnostic
- Low maintenance motors
- Saves valuable time and money

Customer satisfaction guaranteed

- A LIFETIME warranty on blue pre-stretch compound rollers
- A 10-year warranty on 25" sturdy ring gear bearing
- A 3-year unlimited cycle warranty
- Customization of all models through a wide variety of options

Non-proprietary parts on Wulftec machines ensure easy replacement.

Wulftec Semi-Automatic Rotary Arm Machines

All Wulftec machines are designed for optimal productivity, and to give businesses a competitive advantage in a fast-paced marketplace.

Rotary arm models, compared to turntable models, are designed for increased flexibility and for unique load shapes or weights. The rotary arm rotates around

WRT-100

- Economy column mount design
- 25" ring gear bearing drive/support
- 20" NO-THREAD™ powered pre-stretch carriage with 50-300% pre-stretch



SEMI-AUTOMATIC ROTARY ARM MACHINES

ALL Wulftec Semi-Automatic Rotary Arm machines feature common benefits:

- Heavy-duty structural steel construction
- Nema 4/12 control cabinets
 - superior protection against water and dust
 - quick disconnect for easy and fast installation
- Variable rotary arm speed up to 15 RPM
- 40-50 loads per hour
- Easy load positioning
- Unlimited load weight capacity

WRT-125

- Competitively priced
- 20" RAPID-THREAD™ powered pre-stretch carriage with 50-300% pre-stretch
- Expandable freestanding modular design
 - can be easily upgraded to conveyerized or non-conveyerized fully automatic system



WRT MAIN PERFORMANCE FEATURES:

- Separate up and down carriage speeds
- Separate top and bottom wrap selectors (0-9)
 - Wrap patterns can be preset for optimum load containment
- Top cover pause switch
 - Top sheet can be manually inserted for splash proof protection

We're committed to providing superior solutions

To find out more about Wulftec stretch wrap solutions, visit www.wulftec.com or contact your Wulftec Distributor.

a stationary load – a safe, highly effective way of wrapping very light, tall, heavy or unstable loads. Superior safety features are engineered into every

Wulftec machine. Wulftec's exceptional performance characteristics ensure reliability even in the harshest working conditions.

Non-proprietary parts on Wulftec machines ensure easy replacement.



WRT-150

WRT-150

- Free-standing rotary arm with floor mounting integrated design
- 25" ring gear bearing drive/support
- 20" NO-THREAD™ powered pre-stretch carriage with 50-300% pre-stretch
- Rotary arm speed up to 12 RPM
- Ideal in wash-down environments
- Optional hand or motor activated swivel for increased productivity

WRT-200

- Self-supporting four legged design
- Quiet operation
- Counterweighted rotary arm
- Oversize load flexibility
- 25" ring gear bearing drive/support
- 20" NO-THREAD™ powered pre-stretch carriage with 50-300% pre-stretch



WRT-200

Wulftec offers many options.

Wulftec semi-automatic rotary arm models can all be fitted with a wide range of options or engineered to meet any special requirements. Our most popular options include 30" NO-THREAD™ powered pre-stretch carriages, wash-down motors, wrap height and leg extensions.

Technical Specifications



WRT-100	WRT-125	WRT-150	WRT-200
PRODUCTION RATE*			
40-50 loads per hour	40-50 loads per hour	40-50 loads per hour	40-50 loads per hour
LOAD SIZE			
52"W x 52"L x 80"H	58"W x 58" L x 80"H	52"W x 52"L x 80"H	52"W x 52"L x 80"H
LOAD WEIGHT			
Unlimited	Unlimited	Unlimited	Unlimited
OPERATING SYSTEM DIMENSIONS**			
126"W x 132"L x 120"H	119"W x 128"L x 132"H	126"W x 162"L x 120"H	88"W x 150"L x 114"H
SHIPPING WEIGHT			
1,823 lbs.	1,562 lbs.	2,026 lbs.	2,434 lbs.
ELECTRICAL REQUIREMENTS			
<ul style="list-style-type: none"> • 120V/1/60 15A (By Default) • 230V/3/60 10A or 240/1/60 10A (Upon P.O. request) 	<ul style="list-style-type: none"> • 120V/1/60 15A (By Default) • 230V/3/60 10A or 240/1/60 10A (Upon P.O. request) 	<ul style="list-style-type: none"> • 120V/1/60 15A (By Default) • 230V/3/60 10A or 240/1/60 10A (Upon P.O. request) 	<ul style="list-style-type: none"> • 120V/1/60 15A (By Default) • 230V/3/60 10A or 240/1/60 10A (Upon P.O. request)
CONTROLS			
<ul style="list-style-type: none"> • Nema 4/12 control cabinet with quick disconnect • Top cover pause switch (Splash-proof Program) • Spiral up or spiral up/down switch • Autoheight sensing photoeye with on/off switch 	<ul style="list-style-type: none"> • Nema 4/12 control cabinet with quick disconnect • Top cover pause switch (Splash-proof Program) • Spiral up or spiral up/down switch • Autoheight sensing photoeye with on/off switch 	<ul style="list-style-type: none"> • Nema 4/12 control cabinet with quick disconnect • Top cover pause switch (Splash-proof Program) • Spiral up or spiral up/down switch • Autoheight sensing photoeye with on/off switch 	<ul style="list-style-type: none"> • Nema 4/12 control cabinet with quick disconnect • Autoheight sensing photoeye with on/off switch • Spiral up or spiral up/down switch • Top cover pause switch (Splash-proof Program)
FILM DELIVERY SYSTEM			
<ul style="list-style-type: none"> • 20" NO-THREAD™ powered pre-stretch carriage • 50-300% pre-stretch • 1/2 HP AC motor with variable frequency drive for corner compensation 	<ul style="list-style-type: none"> • 20" RAPID-THREAD™ powered pre-stretch carriage • 50-300% pre-stretch • 1/2 HP AC motor with variable frequency drive for corner compensation 	<ul style="list-style-type: none"> • 20" NO-THREAD™ powered pre-stretch carriage • 50-300% pre-stretch • 1/2 HP AC motor with variable frequency drive for corner compensation 	<ul style="list-style-type: none"> • 1/2 HP AC motor with variable frequency drive • 50-300% pre-stretch • 1/2 HP AC motor with variable frequency drive for corner compensation
ROTARY ARM DRIVE			
<ul style="list-style-type: none"> • 25" ring gear bearing drive/support • 12RPM variable speed • 3/4 HP AC motor with variable frequency drive 	<ul style="list-style-type: none"> • Double V-belt and pulley drive rotary arm • 15 RPM variable speed • 1/2 HP AC motor with variable frequency drive 	<ul style="list-style-type: none"> • 25" ring gear bearing drive/support • 12RPM variable speed • 3/4 HP AC motor with variable frequency drive 	<ul style="list-style-type: none"> • 25" ring gear bearing drive/support • 12RPM variable speed • 3/4 HP AC motor with variable frequency drive
STRUCTURE			
Heavy-duty structural steel construction	Heavy-duty structural steel construction	Heavy-duty structural steel construction	Heavy-duty structural steel construction

Note: All machine specifications are subject to change without prior notice. All WRT models require safety fencing.

Nominal dimensions shown.

* Production rate (loads per hour) based on load size and configuration.

** Overall dimensions of the system in operation.

Working closely with customers around the world, Wulftec International is continuously developing and expanding its complete line of automatic and semi-automatic stretchwrap machines – turntable, rotary arm and horizontal.

Whatever the need for a stretchwrapping system, Wulftec has an economy, heavy duty, or custom solution to meet your specific requirements. Choose the options you want; get the rugged efficiency you need.

WULFTEC™
INTERNATIONAL

209 Wulftec,
Ayer's Cliff, Québec
Canada J0B 1C0

Tel.: (819) 838-4232

Toll Free: 1-877-WULFTEC
(985-3832)

Fax: (819) 838-5539

e-mail:
wulftec@wulftec.com

www.wulftec.com

